



ESAK 2 do 8t

Označení	Nosnost		Ø d	a	b	t	Váha
	0°-45°	45°-60°					
	[t]	[t]					
ESAK-2-6-8	2	1,4	18	180	100	264	1,7
ESAK-2-8-8	3,55	2,5	20	180	100	221	1,8
ESAK-2-10-8	5,6	4	22	180	100	231	2,6

ESAK 2 do 16t

Označení	Nosnost		Ø d	a	b	t	Váha
	0°-45°	45°-60°					
	[t]	[t]					
ESAK-2-6-16	2	1,4	20	260	140	360	2,9
ESAK-2-8-16	3,55	2,5	22	260	140	301	2,8
ESAK-2-10-16	5,6	4	26	260	140	311	4,2
ESAK-2-13-16	9,5	6,7	30	260	140	323	6,0
ESAK-2-16-16	14	10	34	260	140	338	9,0

ESAK 2 do 25t

Označení	Nosnost		Ø d	a	b	t	Váha
	0°-45°	45°-60°					
	[t]	[t]					
ESAK-2-6-25	2	1,4	22	340	180	440	3,9
ESAK-2-8-25	3,55	2,5	24	340	180	451	4,6
ESAK-2-10-25	5,6	4	28	340	180	476	7,1
ESAK-2-13-25	9,5	6,7	32	340	180	403	7,7
ESAK-2-16-25	14	10	38	340	180	418	12,2
ESAK-2-18-25	18	12,5	40	340	180	429	14,4

ESAK 2 do 40t

Označení	Nosnost		Ø d	a	b	t	Váha
	0°-45°	45°-60°					
	[t]	[t]					
ESAK-2-6-40	2	1,4	24	430	220	530	5,3
ESAK-2-8-40	3,55	2,5	26	430	220	556	6,9
ESAK-2-10-40	5,6	4	30	430	220	566	9,0
ESAK-2-13-40	9,5	6,7	34	430	220	493	10,5
ESAK-2-16-40	14	10	40	430	220	508	15,2
ESAK-2-18-40	18	12,5	42	430	220	519	18,3
ESAK-2-22-40	26,5	19	48	430	220	534	25,2