







Koeficienty a Nosnosti EN 818-4

	1-pramenný	2-dvoupramenný		3+4-pramenný	
	Nosnosti	Nosnosti		Nosnosti	
Úhel sklonu		0° - 45°	45° - 60°	0° - 45°	45° - 60°
Rozměr řetězového článku					
[mm]	[t]	[t]		[t]	
6 x 18	1,12	1,6	1,12	2,36	1,7
7 x 21	1,5	2,12	1,5	3,15	2,24
8 x 24	2	2,8	2	4,25	3
10 x 30	3,15	4,25	3,15	6,7	4,75
13 x 39	5,3	7,5	5,3	11,2	8
16 x 48	8	11,2	8	17	11,8
18 x 54	10	14	10	21,2	15
20 x 60	12,5	17	12,5	26,5	19
22 x 66	15	21,2	15	31,5	22,4
26 x 78	21,2	30	21,2	45	31,5
28 x 84	25	33,5	25	50	37,5
32 x 96	31,5	45	31,5	67	47,5
36 x 108	40	56	40	85	60
40 x 120	50	71	50	106	75
45 x 135	63	90	63	132	95
Koeficient		1,4	1	2,1	1,5

	Nosnosti	Nosnosti		Nosnosti	
	Nosnosti	0° - 45°	45° - 60°	0° - 45°	45° - 60°
Úhel sklonu		0° - 45°	45° - 60°	0° - 45°	45° - 60°
Rozměr řetězového článku					
[mm]	[t]	[t]	[t]	[t]	[t]
6 x 18	1,8	1,25	0,9	1,9	1,32
7 x 21	2,5	1,7	1,25	2,65	1,8
8 x 24	3,15	2,24	1,6	3,35	2,36
10 x 30	5	3,35	2,5	5,3	3,75
13 x 39	8,5	5,83	4,25	9	6,3
16 x 48	12,5	9	6,3	13,2	9,5
18 x 54	16	11,2	8	17	11,8
20 x 60	20	14	10	21,2	15
22 x 66	23,6	17	11,8	25	18
26 x 78	33,5	23,6	17	35,5	25
28 x 84	40	26,5	20	42,5	30
32 x 96	50	35,5	25	53	37,5
36 x 108	63	45	31,5	67	47,5
40 x 120	80	56	40	85	60
45 x 135	100	71	50	106	75
Koeficient	1,6	1,1 (1,4)*	0,8 (1)*	1,7 (2,1)*	1,2 (1,5)*