



TASGV-4 do 8 t

Označení	Nosnost		Ø d	a	t	Ø d ₁	t	Váha
	0°-45°	45°-60°						
	[t]	[mm]						
TASGV-4 - 6-8 t	2,36	1,7	20	180	100	16	280	2,6
TASGV-4 - 8-8 t	4,25	3	22	180	100	16	291	3,4

TASGV-4 do 16 t

Označení	Nosnost		Ø d	a	b	Ø d ₁	t	Váha
	0°-45°	45°-60°						
	[t]	[mm]						
TASGV-4 - 6-16 t	2,36	1,7	22	260	140	16	360	3,4
TASGV-4 - 8-16 t	4,25	3	26	260	140	18	386	5,2
TASGV-4 - 10-16 t	6,7	4,75	30	260	140	18	395	7,2
TASGV-4 - 13-16 t	11,2	8	34	260	140	22	438	11,4

TASGV-4 do 25 t

Označení	Nosnost		Ø d	a	b	Ø d ₁	t	Váha
	0°-45°	45°-60°						
	[t]	[mm]						
TASGV-4 - 6-25 t	2,36	1,7	24	340	180	16	440	4,7
TASGV-4 - 8-25 t	4,25	3	28	340	180	18	466	8,25
TASGV-4 - 10-25 t	6,7	4,75	32	340	180	18	475	8,9
TASGV-4 - 13-25 t	11,2	8	38	340	180	22	518	14,2
TASGV-4 - 16-25 t	17	11,8	42	340	180	26	557	19,8

TASGV-4 do 40 t

Označení	Nosnost		Ø d	a	b	Ø d ₁	t	Váha
	0°-45°	45°-60°						
	[t]	[mm]						
TASGV-4 - 6-40 t	2,36	1,7	26	430	220	16	530	6,2
TASGV-4 - 8-40 t	4,25	3	30	430	220	18	556	8,7
TASGV-4 - 10-40 t	6,7	4,75	34	430	220	22	595	12,5
TASGV-4 - 13-40 t	11,2	8	40	430	220	26	633	18,8
TASGV-4 - 16-40 t	17	11,8	42	430	220	26	647	23,5
TASGV-4 - 18-40 t	21,2	15	48	430	220	32	669	33,2
TASGV-4 - 22-40 t	31,5	22,4	54	430	220	36	704	64