



TASGV-2 do 8t

t

Označení	Nosnost		Ø d	a	b	Ø d ₁	t	Váha
	0°-45°	45°-60°						
	[t]	[mm]						
TASGV-2 - 6-8t	1,6	1,12	18	180	100	13	264	1,70
TASGV-2 - 8-8t	2,8	2	20	180	100	-	221	1,86
TASGV-2 - 10-8 t	4,25	3,15	22	180	100	-	230	2,60

TASGV-2 do 16t

Označení	st		Ø d	a	b	Ø d ₁	t	Váha
	0°-45°	45°-60°						
	[t]	[mm]						
TASGV-2 - 6-16t	1,6	1,12	20	260	140	16	360	2,90
TASGV-2 - 8-16t	2,8	2	22	260	140	-	301	2,80
TASGV-2 - 10-16 t	4,25	3,15	26	260	140	-	310	4,10
TASGV-2 - 13-16 t	7,5	5,3	30	260	140	-	323	6,00
TASGV-2 - 16-16 t	11,2	8	34	260	140	-	337	8,92

TASGV-2 do 25t

Označení	st		Ø d	a	b	Ø d ₁	t	Váha
	0°-45°	45°-60°						
	[t]	[mm]						
TASGV-2 - 6-25t	1,6	1,12	22	340	180	16	440	3,90
TASGV-2 - 8-25t	2,8	2	24	340	180	16	451	4,60
TASGV-2 - 10-25 t	4,25	3,15	28	340	180	18	475	6,90
TASGV-2 - 13-25 t	7,5	5,3	32	340	180	-	403	7,80
TASGV-2 - 16-25 t	11,2	8	38	340	180	-	417	12,10
TASGV-2 - 18-25 t	14	10	40	340	180	-	429	14,20

TASGV-2 do 40t

Označení	st		Ø d	a	b	Ø d ₁	t	Váha
	0°-45°	45°-60°						
	[t]	[mm]						
TASGV-2 - 6-40t	1,6	1,12	24	430	220	16	530	5,30
TASGV-2 - 8-40t	2,8	2	26	430	220	18	556	6,70
TASGV-2 - 10-40 t	4,25	3,15	30	430	220	18	565	8,80
TASGV-2 - 13-40 t	7,5	5,3	34	430	220	-	493	10,30
TASGV-2 - 16-40 t	11,2	8	40	430	220	-	507	15,00
TASGV-2 - 18-40 t	14	10	42	430	220	-	519	18,32
TASGV-2 - 22-40 t	21,2	15	48	430	220	-	534	25,40